(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 22 February 2001 (22.02.2001)

PCT

(10) International Publication Number WO 01/13438 A1

(51) International Patent Classification⁷: 35/32, G01K 7/02

H01L 35/00.

- (21) International Application Number: PCT/ZA00/00136
- (22) International Filing Date: 16 August 2000 (16.08.2000)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 99/5203


16 August 1999 (16.08.1999) Z

- (71) Applicant (for all designated States except US): TEM-PERATURE MANAGEMENT SYSTEMS (PROPRI-ETARY) LIMITED [ZA/ZA]; 42 Ceramic Curve, Alton, Richards Bay, 3900 Kwa-Zulu Natal (ZA).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): GRAY, Adrian, Lionel [ZA/ZA]; 42 Ceramic Curve, Alton, Richards Bay, 3900 Kwa-Zulu Natal (ZA).

- (74) Agent: JOHN & KERNICK; An Intellectual Property Office of Bowman Gilfillan Inc., P.O. Box 3511, 1685 Halfway House (ZA).
- (81) Designated States (national): AE, AG, AL, AM, AT, AT (utility model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, CZ (utility model), DE, DE (utility model), DK, DK (utility model), DM, DZ, EE, EE (utility model), ES, FI, FI (utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KR (utility model), KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: METALLURGICAL THERMOCOUPLE



(57) Abstract: This invention concerns a thermocouple which is protected by an outer sheath consisting of inner and outer tubes with the annular space filled with low temperature sintering refractory material which is preferably beaded before filling in the space and in which the outer tube is constricted to compact the material. The refractory material will include borosilicate and boric acid powder.



01/13438 A1